



NOTES:

- CONTACT CURRENT RATING: 0.3A.
- CONTACT RESISTANCE: 50 mΩ MAX.;
- INSULATION RESISTANCE: 1000Ω MIN.;
- DIELECTRIC WITHSTANDING: 300V AC MIN.;
- DURABILITY: 10000 CYCLES MIN.;
- CONNECTOR MATING FORCES: 20N (2.04Kgf) MAX.;
- CONNECTOR UNMATING FORCES: 3N(0.31Kgf) MIN.;
- PRODUCT MEET THE REQUEST OF THE RoHs, SEE TABLE A:

TABLE A:

MATTER	RoHs (PPM)
Cd	≤ 100
Pb	≤ 1000
Hg	≤ 1000
Cr6+	≤ 1000
PBB	≤ 1000
PBDE	≤ 1000

UNLESS OTHERWISE SPECIFIED TOLERANCES U.S. METRIC .X +/- 0.25 .XX +/- 0.15 .XXX +/- FRACTIONS +/- ANGLES +/- 0.5° FOR MATERIALS AND FINISHES SEE NOTES REMOVE SHARP EDGES DIMENSIONS U.S. INCHES (METRIC) (MM)	APPROVAL		DATE
	DRAWN		
	CHECKED		
	CHECKED		
	DRAWING FILE :		
	ANGLE OF PROJECTION		

HDC 有限公司			
TITLE 3 PIN BATTERY CONNECTOR			
SIZE	DRAWING NO.	REV.	
A3	03-01	A	
SCALE	NONE	SHEET 1 OF 1	

ITEM	PART NAME	Q'TY	MATERIAL	DESCRIPTION	REMARK
2	HOUSING	1	LCP	Black	UL 94 V-0
1	TERMINAL A	3	Beryllium Copper	Gold Plated	