


WIRE CONNECTION

P1	COLOR	P2
1	RED	A4,B4,A9,B9
2	WHITE	A7
3	GREEN	A6
4	BLACK	A1,B1,A12,B12



TEST REQUEST:

- 1.OPEN SHORT 100%
- 2.CT ≤ 2Ω IS ≥ 5MΩ
- 3.HV:DC 300V TIME: 0.1SEC

ITEM LIST

NO.	ITEM	DESCRIPTION	AMOUNT
①	CABLE	UL2725 26#(7/0.16TC)*2C(RED, BLACK)+28#*1P(WHITE, GREEN)+D(7/0.12TS)+AL.OD:3.7mm COLOR:BLACK PVC L=1000mm	1PCS
②	CONN	USB A/M PBT WHITE SHELL NI 三件式	1PCS
③	CONN	Type C (2.0) Male Connector, Terminal Gold-Plated, Shell Nickel Plated, Insulator Color:Black(SC-2 5.6K)	1PCS
④	PVC	45P PVC COLOR:BLACK	8g
⑤	PE	LD-PE	1PCS
⑥	MINI TIE	L=80mm BLACK OVAL TIE	1PCS
⑦	骨袋	150*60MM 印黑色环保标示, 印MADE IN CHINA	1PCS

DRAWN BY	<i>Famous</i>	CUSTOMER	HDC 有限公司
CHECKED			
APPROVED			
TITLE		USB AM TO TYPE-C	
-TOLERANCES- X.X±0.5 X.XX±0.10 ANGLES ±5		THIRD ANGLE PROJECTION	
1X	ORIGINAL	SHEET: 1/1	DRAWING NO: JS003478
REV	DESCRIPTION	UNIT: mm	DATE: FEB-02-2018
APVD	ECO NO.		REV. 1X