

Specification

MATERIAL:
 Insulation: High Temperature Thermoplastic, Color: Black JIS 94V-0
 Contact: Phosphor-Bronze
 Shell: Brass

PLATING:
 Contact: Plated 50 μ Ni Over
 Plated Au Selective Contact Area
 Plated 100 μ Sn Over Ni Sn Solder Area
 Shell: Plated 50 μ Ni Over
 Plated Au Selective Solder Area

Electrical:
 Current Rating: 0.50A max
 Contact Resistance: 100m Ω max.
 Insulation Resistance: 1000M Ω min./1000VDC
 Dielectric Withstanding Voltage: 200VAC/1 minute
 Operating Temperature: -25 $^{\circ}$ C to +85 $^{\circ}$ C
 Mounting Spikes: 10,000 operations

Usable Memory Card: micro SD Card

- PART NUMBER:**
 MS-12701-000-0
- 1: For Au 10 μ Plating
 - A: For Au 50 μ Plating
 - B: For Au 15 μ Plating
 - C: For Au 30 μ Plating



REV	REVISE	REVISE	REVISE
NO.	DESCRIPTION	DATE	BY
01	FOR THE FIRST TIME	2011.08.15	W. H.
02	FOR THE SECOND TIME	2011.08.15	W. H.

HDC 有限公司

REV	REVISE	REVISE	REVISE
NO.	DESCRIPTION	DATE	BY
01	FOR THE FIRST TIME	2011.08.15	W. H.
02	FOR THE SECOND TIME	2011.08.15	W. H.

1

2

3

4

5



6

7

A

PIN ASSIGNMENT:

RECOMMEND PCB LAYOUT (Dimension: X & Y: 0.15mm, Z: 0.05mm, X0X & 0.40)



PIN NO.	PIN ASSIGNMENT
1P	NC
2P	CC/CH12
3P	CS0
4P	SD0
5P	CS1
6P	SD1
7P	CS2
8P	SD2

3anaTrade.com
02-2163-0766

E

HDC 有限公司

REV.	CHANGE	REVISION	DATE
01	020-10701-000-0	020-10701-000-0	02/01/01
02	020-10701-000-0	020-10701-000-0	02/01/01

料號	020-10701-000-0	物料名稱	020-10701-000-0	圖號	020-10701-000-0
規格	16PIN	規格	16PIN	圖號	020-10701-000-0
單位	個	單位	個	圖號	020-10701-000-0
備註		備註		圖號	020-10701-000-0

