



	PJ20300-J (PJ-230)	PJ20300-M (PJ-230-1)	PJ20300-B (PJ-230-2)	PJ20300-D (PJ-230-3)
①	○ 1 ②	○ 1 ②	○ 1 ⑤	○ 1 ⑤
②	√ ○ 4 ⑤	√ ○ 4 ⑤	√ ○ 4 ④	√ ○ 4 ④
③	√ ○ 3 ④	√ ○ 3 ④	√ ○ 3 ④	√ ○ 3 ④
④	√ ○ 3 ④	√ ○ 3 ④	√ ○ 3 ④	√ ○ 3 ④
⑤	√ ○ 3 ④	√ ○ 3 ④	√ ○ 3 ④	√ ○ 3 ④
⑥	√ ○ 3 ④	√ ○ 3 ④	√ ○ 3 ④	√ ○ 3 ④
⑦	√ ○ 3 ④	√ ○ 3 ④	√ ○ 3 ④	√ ○ 3 ④

SPECIFICATION

1. Rating ? DC 30V 0.5A?
2. Contact resistance $\leq 30m\Omega$?
3. Insulation resistance $\geq 100M\Omega$ (DC250V)?
4. Withstand voltage $\geq 500VAC$?
5. Insertion and extraction force $\leq 25N$;
6. life test $\geq 5,000$ cycles

Ordering information:

PJ20300-??B-??-§-??-?

① ② ③ ④ ⑤ ⑥ ⑦

- ①: Series No
- ②: Schematic option: J, M, B, D
- ③: Material of housing:
PB=PBT (standard)
- ④: Housing color:
0A=Black
1_=Brown 2_=Red 3_=Orange
4_=Yellow 5_=Green 6_=Blue
7_=Purple 8_=Gray 9_=White
- ⑤: Terminal plating
S: Silver (Ag) (standard)
- ⑥: Special option:
00: No special option
- ⑦: Packing mode:
4: Bag packing (standard)

NO.	DESCRIPTION	QTY	MATERIAL	PART NO.	PLATING
⑥	Shunt terminal	1	C2680-1/2H	PJ20300-05 (PP-778)	Ag-Plating
⑤	Ring spring	1	C5210-EH	PJ20300-04 (JA-779)	Ag-Plating
④	Ring spring	1	SUS301-3/4H	PJ20300-03 (TP-777)	Ag-Plating
③	Tip spring	1	C5210-EH	PJ20300-02 (TP-776)	Ag-Plating
②	Earth spring	1	C5210-EH	PJ20300-01 (JA-780)	Ag-Plating
①	Housing	1	PBT	PJ20300-S1 (ST-775)	

UNIT:MM	TYPE:	MODEL NO:	PAPER NO: A4	PAGE 1 OF 1
⊕	∅2.5 PHONE JACK	20300-__PB__S__	TOLERANCE	ANGLES
			±0.3	±2°
DESIGNER BY:	Bingo	2008.08.30	SCALE	VER
CHECK BY:			FULL	3
APPROVED BY:				

HDC有限公司