



RECOMMENDED PITCH LAYOUT
UNSPECIFIED TOLERANCE:±0.05
(TOP VIEW)

Ordering information:
PJ30340 ? PB S 00 3
(1) (2) (3)(4)(5)(6)(7)

- (1):Series No.
- (2):Schematic option:
A?B?C?D?F?G?H?K
L?M?N?W?P?S?T?Q
- (3):Material of housing:
PB=PBT
- (4):Housing color:
0A=Black 0R=White
- (5):Terminal plating:
S=Silver(Ag)
- (6):Special option:
00=No special option
- (7):Packing mode:
3=Plastic box pack

- Specification:
- 1.Rating ?DC 30V 0.5A?
 - 2.Contact resistance?≤30m??
After test:≤50m?
 - 3.Insulation resistance??100M?(500VDC)?
After test:50M?
 - 4.Withstand voltage?500VAC ?
 - 5.Insertion and extraction force?3N?30N?
 - 6.life test?5000cycles min?
 - 7.Operation temperature range?20-70?
 - 8.Preservation temperature range?40-70?

REV.	Q'TY	ECN.	NO.	REASON&CONTENTS	SIGN	DATE
4	△			Add the housing color type	MEIYANGYONG	1.09.27

Model No.	PJ30340-A	PJ30340-B	PJ30340-C	PJ30340-D	PJ30340-F
Schematic					
Model No.	PJ30340-G	PJ30340-H	PJ30340-K	PJ30340-L	PJ30340-M
Schematic					
Model No.	PJ30340-N	PJ30340-W	PJ30340-P	PJ30340-S	PJ30340-T
Schematic					
Model No.	PJ30340-Q				
Schematic					

9	Make terminal	2	Copper alloy	PJ30340-08	Silver plating
8	Break terminal	2	Copper alloy	PJ30340-04	Silver plating
7	Transfer spring	2	Copper alloy	PJ30340-05	Silver plating
6	Ring spring	1	Copper alloy	PJ30340-03	Silver plating
5	Tip spring	1	Copper alloy	PJ30340-02	Silver plating
4	Earth spring	1	Copper alloy	PJ30340-01	Silver plating
3	Insulator	1	Thermoplastic	PJ30340-S4	White
2	Cover	1	Thermoplastic	PJ30340-S2	White
1	Housing	1	Thermoplastic	PJ30340-S1	

THIS DOCUMENT IS THE SOLE PROPERTY OF BSRN ELECTRONICS CO., LTD. AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.	UNIT:MM	TOLERANCE	TYPE:	MODEL NO:	DRAWING TYPE:	
		DIMENSIONS	Ø3.5 PHONE JACK	PJ30340-_PB_ _S003	CUSTOMER DRAWING	
		ANGLES				
DESIGNER BY:	CHECK BY:	APPROVED BY:	DRAWING No:	SCALE:	VER.:	PAGE:
			BSCR-0000-0024	1:1	04	1/1

HDC有限公司