



Ordering information:

PJ3080A -

- ①: Series No.
- ②: Schematic option: D
- ③: Material of housing: 9T=PA9T
- ④: Bushing or Housing color: 0A=Black (Standard)
- ⑤: Terminal plating S: Silver(Ag) ; G: Gold(Au)
- ⑥: Special option: 00: No special option
- ⑦: Packing mode: 1: Reel packing, 4: Bag packing

Model NO.	PJ3080A-D
Schematic	

: TERMINAL NO. : ITEM NO.

SPECIFICATION
 1. Rating : DC 30V 1A;
 2. Contact resistance: $\leq 30m\Omega$;
 3. Insulation resistance: $\geq 100M\Omega$ (DC250V);
 4. Withstand voltage: 500VAC ;
 5. Insertion and extraction force: 3-30N;
 6. life test: 5,000 cycles.

③	Tip spring	1	Bronze t=0.2	PJ3080A-02	Ag/Au-Plating
②	Earth terminal	2	Bronze t=0.2	PJ3080A-01	Ag/Au-Plating
①	Housing	1	PA9T UL94V-0	PJ30800-S1(ST-890)	
NO.	DESCRIPTION	QTY	MATERIAL	PART NO.	PLATING
UNIT: MM		TYPE:		MODEL NO:	PAPER NO: A4
		3.5 PHONE JACK		PJ3080A-D9T0A _ 00 _	PAGE 1 OF 1
DESIGNER BY:		Li Wenhui 2008.9.2		TOLERANCE	ANGLES
CHECK BY:				±0.3	±2'
APPROVED BY:				SCALE	VER
				FULL	1

H D C 有限公司