



P.C.B LAYOUT

MATERIALS AND FINISH

SHELL : STEEL MATERIAL, TIN FINISHED
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED, UL 94V-0 RATED, BLACK COLOR
 CONTACT MATERIAL : BRASS
 CONTACT FINISH : SELEVITE GOLD FINISHED
 RIVETED INSERT: BRASS MATERIAL, TIN FINISHED
 JACK SCREWS : BRASS MATERIAL, NICKEL FINISHED WITH #4-40 THREADED ASSEMBLED

ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS
 CONTACT RESISTANCE : 30 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.
 TEMPERATURE RATING : -55°C ~ +105°C

Tolerance	Drawn by	
Dimensions	Designed by	
X. ±0.38	Approved by	
X.X ±0.35	DWG NO. CP-024	Scale 1:1
XXX ±0.25	Sheet 1 of 1	Unit mm
XXXX ±0.15	REV A0	
Angle		
X.° ±2°		
X.X° ±1.0°		
XXX° ±0.5°		

HDC 有限公司

DESC.: HDB15F 铆鱼叉锁螺丝
 鱼叉15.00 端子8.00

PART NO.: