



## MATERIALS AND FINISH

SHELL : STEEL MATERIAL, NICKEL FINISHED  
 DIMPLES ON PLUG ONLY  
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS  
 FILLED, UL 94V-0 RATED, BLACK COLOR  
 CONTACT MATERIAL : BRASS  
 CONTACT FINISH : SELECTIVE GOLD FINISHED  
 GROUNDING BRACKET : BRASS MATERIAL, TIN PLATED  
 DIE CASTING BRACKET : ZINC ALLOY, NICKEL PLATED  
 JACK SCREWS : NICKEL FINISH  
 WITH #4-40 THREADED ASSEMBLED

## ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS  
 CONTACT RESISTANCE : 30 MILLIOHMS MAX.  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.  
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.  
 TEMPERATURE RATING :  $-55^{\circ}\text{C} \sim +105^{\circ}\text{C}$

H D C 有限公司

 UNLESS OTHERWISE SPECIFIED TOLERANCE Inch: .000 = $\pm 0.01$ .0000 = $\pm 0.0050$ mm: .00 = $\pm 0.25$ .000 = $\pm 0.130$ Ang: 0.0 = $\pm 2^{\circ}$	Drawer	Zhaoliang	Product	D-SUB
	Designer	Zhaoliang	Type	DUAL-PORT
Approved	Xie pengchi	Description	A15S/A15P	
Unit	mm/inch	Scale	1:1	No.
Date	98.01.22	Ver	A	Cad No.
				150-C30-601-012
				Z401012

P.C.B LAYOUT