


REV.	ECN NO.	DESCRIPTION	DRAW	CHECK	APPD.	DATE
X0		新发行	xu dong bin	David	y.x.l	09-02-28

NOTES:

- MECHANICAL:
 - MATING: 35N MAX.
 - WITHDRAWAL: 10N MIN.
 - DURABILITY: 1500 CYCLES MIN.
- ELECTRICAL:
 - CURRENT: 1.8A MAX For Pin1 And Pin4 and 0.25A for all the other pins
 - VOLTAGE: 30V MAX
 - WITHSTANDING VOLTAGE: 100V AC
 - CONTACT RESISTANCE: 30 mΩ MAX
 - INSULATION RESISTANCE: 100MΩ MIN
- ENVIRONMENTAL
 - TEMPERATURE RANGE -55°C ~ +85°C
- OTHER:
 - PRODUCT MEET ROHS STANDARD

Table:

PRODUCT NO.	TEM	PART NO.	PART NAME	Q'TY	Material
CN754U050P	1	PS208B3540	FRONT SHELL	1	SPCC,NI 80U" MIN
	2	PS208B3550	BACK SHELL	1	SPCC,OD=6.0,NI 80U" MIN
	3	PS105B1730	CONTACT 1	4	C2680R-H,GOLD 5U"
	4	PS105B1740	CONTACT 2	5	C2680R-H,GOLD 5U"
	5	CN754U0501	SEMI-PRODUCT	1	PBT+30%GF,BLUE,GOLD 5U"
CN754U060P	3	PS106B1730	CONTACT 1	4	C2680R-H,GOLD 15U"
	4	PS106B1740	CONTACT 2	5	C2680R-H,GOLD 15U"
	5	CN754U0601	SEMI-PRODUCT	1	PBT+30%GF,BLUE,GOLD 15U"
CN754U030P	3	PS103B1730	CONTACT 1	4	C2680R-H,GOLD 30U"
	4	PS103B1740	CONTACT 2	5	C2680R-H,GOLD 30U"
	5	CN754U0301	SEMI-PRODUCT	1	PBT+30%GF,BLUE,GOLD 30U"
CN754U051P	1	PS202B3540	FRONT SHELL	1	SPCC,GOLD FLASH
	2	PS202B3550	BACK SHELL	1	SPCC,OD=6.0,GOLD FLASH

UNITS mm	SCALE 1:1	REV. X0	SHEET 1 OF 1
		DATE 2009-02-28	
GENERAL TOLERANCE		DR. xu dong bin	
0.	±0.30	CHK. David	
0.0	±0.25	APPD. Y.X.L	
0.00	±0.25		
0.*	±4*		
0.0*	±2*		

HDC 有限公司			
TITLE: GUSB-L3022			
MAT'L SEE TABLE		FINISH SEE TABLE	
DWG.NO. DWG-USB AM-126	A	PART NO. SEE TABLE	SIZE A4

