


Electrical  
 Voltage: 5.0 V  
 Current: 0.5 A  
 Contact Resistance: Terminal 50 milliohms max-shell and Terminal  
 Isulation Resistance: 100 Megohms min  
 Dielectric Withstanding Voltage: 100 V AC/1 min  
 Temperature: -40℃~85℃

MN044-

颜色 (主体)	材质 (主体)	外壳镀层	端子镀层 (接合处)
1: 黑色 6: 绿色	1: PBT 2: LCP	1: 全金 6: 前镍后锡	1: 1U" 6: 30U"
2: 白色 7: 红色	3: NL9T 4: NL6T	2: 全镍 0: 其它	2: 3U" 0: 其它
3: 贝吉色 0: 其它	5: ABS 6: NL66	3: 全锡	3: 5U"
4: 灰色	7: PPS 8: PVC	4: 前金后锡	4: 10U"
5: 蓝色	9: PE 0: 其它	5: 前金后镍	5: 15U"



TOLERANCE				
SELECT	TOL	1	2	3
ON				✓
0.000+/-	0.02	0.05	0.10	
0.00 +/-	0.05	0.10	0.15	
0.0 +/-	0.10	0.15	0.20	
0 +/-	0.15	0.20	1.00	
ANGLE +/-	1.0	1.0	1.5	

NO.	PART NAME	MATERIALS	THICKNESS	QTY	REMARK
3	CONTACT	C5191	0.20mm	5	Z0001
2	HOUSING	LCP		1	Z0001
1	STEEL	C2680	0.25mm	1	Z0001

设计 杨涛 审核  
 DRAW BY 杨涛 DISCUSS BY  
 校对 比例 2:1  
 DISCUSS BY SCALE

HDC 有限公司

图名 MICRO USB 5PM B 图号 日期 2006.08.20  
 DRAWING NO SHEET NO DATE  
 备注 版次 备注 版次 张数 1/1  
 VERSION QUAN REMARK REMARK SHEET