



规格说明: Specifications:
电气特性: Electrical:

1. 额定电流: Current Rating
1.0A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
50 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
300 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
100 MEGA ohms MIN

物理性能: Physical properties:

1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.0kgf (MAX)
Unmate force: 0.7kgf (MIN)
2. 端子保持力: Terminal retention force
0.5kgf (MIN)

原材料: Raw material:

1. 塑胶: Plastic cement:
Hing Temperature Thermoplastics,
UL 94V-0 LCP Black
2. 端子: Contact: Copper Alloy C5191
3. 外壳: Shell: Copper Alloy C2680

电镀: Electroplate:

1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Talls
2. 外壳: Shell:
Nickel Plating

UNITS mm	SCALE 1:1	REV. B3	SHEET 1 OF 1		
		DATE 2011.10.18	TITLE		
GENERAL TOLERANCE		DR. Apovi	MINI USB 8F SMT 双倒角前贴后插		
0. ±0.30 0.0 ±0.20 0.00 ±0.15 0.° ±4° 0.0° ±2°		CHK. Zhu	MAT'L YANG	FINISH	
		APPD. YANG	DWG.NO. MN069-1	A	PART NO. SEE TABLE
					SIZE A4