



1. 电气性能:
 额定电流: 1.0A/CONTACT-
 额定电压: 30V DC
 耐电压: 100V AC MIN
 接触阻抗: 30M Ω MAE 耐久后40M Ω
 绝缘阻抗: 100M Ω MIN
 工作温度: -30° TO+80°

2. 机械性能:
 插入力: 35N MAX
 拔出力: 10N MIN 耐久后8N MIN 20N MAX
 端子保持力: 1.0KGf MIN
 耐久次数: 10000MIN.

MN138-4-

颜色 (主体)	材质 (主体)	外壳镀层	端子镀层 (接合处)
1: 黑色 2: 白色 3: 贝吉色 4: 灰色 5: 蓝色	6: 绿色 7: 红色 0: 其它	1: PBT 2: LCP 3: NL9T 4: NL6T 5: ABS 6: NL66 7: PPS 8: PVC 9: PE 0: 其它	1: 全金 2: 全镍 3: 全锡 4: 前金后锡 5: 前金后镍
		6: 前镍后锡 0: 其它	1: 1U" 2: 3U" 3: 5U" 4: 10U" 5: 15U" 6: 30U" 0: 其它

TOLERANCE			
SELECT	1	2	3
ON TOL			✓
0.000+/-	0.05	0.10	0.15
0.00 +/-	0.10	0.20	0.25
0.0 +/-	0.10	0.15	0.20
0 +/-	0.15	0.20	0.30
ANGLE+/-			0.35

NO.	PART NAME	MATERIALS	THICKNESS	QTY	REMARK
3	CONTACT	C2680	0.20mm	5	Z0001
2	HOUSING	LCP		1	Z0001
1	STEEL+HOOK	SUS201	T=0.2mm TO.35	1	Z0001

设计 DRAW BY	杨涛	审核 DISCUSS BY	
校对 DISCUSS BY		比例 SCALE	2:1

HDC电子有限公司

图名 DRAWING NO	MICRO USB 5PM B	图号 SHEET NO	MU138-4	日期 DATE	2006.08.20
备注 VERSION		版次 QUAN		张数 SHEET	1/1