



SPECIFICATIONS:

Contact current Rating:1Amperes.
 DIELECTRIC Withstanding Voltage:AC 500V.
 Insulation resistance:1000MΩ Minimum.
 Contact Resistance:30mΩ Maximum.
 operating Temperature:-45℃ to +85℃.

MECHANICAL CHARACTERISTICS:

Mating Force:3.5Kg. Maximum.
 Unmating Force:1kg. Minimum.
 durability:1500 cycles.

Enviromental

*Recommended PC Board Thickness:1.6±0.05mm.

UB004-3NEW

颜色 (主体)		材质 (主体)		外壳镀层		端子镀层 (接合处)	
1: 黑色	6: 绿色	1: PBT	2: LCP	1: 全金	6: 前镍后锡	1: 1U"	6: 30U"
2: 白色	7: 红色	3: NL9T	4: NL6T	2: 全镍	0: 其它	2: 3U"	0: 其它
3: 贝吉色	0: 其它	5: ABS	6: NL66	3: 全锡		3: 5U"	
4: 灰色		7: PPS	8: PVC	4: 前金后锡		4: 10U"	
5: 蓝色		9: PE	0: 其它	5: 前金后镍		5: 15U"	

TOLERANCE			
SELECT	TOL		
IN	1	2	3
0.000+/-	0.02	0.05	0.10
0.00 +/-	0.05	0.10	0.15
0.0 +/-	0.10	0.15	0.20
0 +/-	0.15	0.20	1.00
ANGLE +/-	1.0	1.0	1.5

No.	PART NAME	DESCRIPTION	THICKNESS	QTY	SUPPLIER
1	HOUSING	PBT	WT/ BK	1	Z0006
2	CONTACT	C2680	Au:G/F Sn: 100u" Ni:40u"	4	Z0001
3	SHELL	SPCC	NI 50-80u	1	Z0005

设计 DRAW BY	杨帆	审核 DISCUSS BY	
校对 DISCUSS BY		比例 SCALE	2:1

图名 DRAWING NO	USB BF DIP 90度		图号 SHEET NO	UB004-3NEW	日期 DATE	2020-8-31
备注 VERSION	版次 QUAN		备注 REMARK	版次 REMARK	张数 SHEET	1/1